

Cinelex SKYNODE-RDM

Plug & Play Wireless DMX Receiver with RDM

WIRELESS DMX, FOR ANY LIGHT

Add wireless DMX functionality to any DMX-capable light.

SIMPLE SETUP

Link to a LumenRadio transmitter with a single button-press.

RDM SUPPORT

Enable two-way communication between light fixture & RDM-compatible controller.

SMALL, YET MIGHTY

Compact design ensures clean integration with any light.

PROFESSIONAL READY

Robust materials make SKYNODE ready for tough rental & on-set environments.

USB-POWERED

Power SKYNODE from any 5V USB source.



Wireless Protocol

Protocol	LumenRadio
Operational Frequency	2.4GHz (2402-2480MHz)
Range	Up to 100m (environment dependent)
DMX Standards	DMX512, DMX512 (1990) & DMX512-A

Power

Micro-USB	5V
Power Consumption	1W

Connectors

- 1x DMX XLR 5-Pin Female
- 1x Micro-USB Power Input Female
- 1x Built-In Antennae

LED Indicators

1x "STATUS" LED	Connection Status
1x "POW" LED	Power Input Confirmation
3x Signal Strength LEDs	Signal Strength Indicator

Size (with Antennae)

Weight	53g
Dimensions	80mm x 26mm x 38mm (L x W x D)

W - www.cinelex.tv | E - info@cinelex.tv | T - +44 (0) 1784 450 506
Cinelex, Unit 10, Sky Business Park, Eversley Way, Egham, TW20 8RF, UK